

(i) Coordinate with the affected subsequently-filed U.S. DBS space station operator all of its operations that are either in excess of the pfd level calculated on the basis of the predicted antenna off-axis gain data, or are in excess of the threshold pfd level of -117 dBW/m²/100 kHz, whichever is greater, or

(ii) Adjust its operating parameters so that at the location of the subsequently-filed U.S. DBS space station, either the pfd level calculated on the basis of the predicted off-axis transmitting antenna gain data, or the threshold pfd level of -117 dBW/m²/100 kHz, whichever is greater, is not exceeded.

(3) No coordination or adjustment of operating parameters is required in cases where the DBS and 17/24 GHz BSS operating frequencies do not overlap.

(f) The 17/24 GHz BSS applicant or licensee must modify its license, or amend its application, as appropriate, based upon new information:

(1) If the pfd levels submitted in accordance with paragraph (d) of this section, are in excess of those submitted in accordance with paragraph (b) of this section at the location of any prior-filed or subsequently-filed U.S. DBS space station as defined in paragraphs (b)(1) and (d)(1) of this section, or

(2) If the 17/24 GHz BSS operator adjusts its operating parameters in accordance with paragraphs (e)(1)(ii) or (e)(2)(ii) or this section.

(g) Absent an explicit agreement between operators to permit more closely spaced operations, U.S. authorized 17/24 GHz BSS space stations and U.S. authorized DBS space stations with co-frequency assignments may not be licensed to operate at locations separated by less than 0.2 degrees in orbital longitude.

(h) All operational 17/24 GHz BSS space stations must be maintained in geostationary orbits that:

(1) Do not exceed 0.075° of inclination.

(2) Operate with an apogee less than or equal to 35,806 km above the surface of the Earth, and with a perigee greater than or equal to 35,766 km above the surface of the Earth (*i.e.*, an eccentricity of less than 4.7×10^{-4}).

(i) U.S. authorized DBS networks may claim protection from space path

interference arising from the reverse-band operations of U.S. authorized 17/24 GHz BSS networks to the extent that the DBS space station operates within the bounds of inclination and eccentricity listed below. When the geostationary orbit of the DBS space station exceeds these bounds on inclination and eccentricity, it may not claim protection from any additional space path interference arising as a result of its inclined or eccentric operations and may only claim protection as if it were operating within the bounds listed below:

(1) The DBS space station's orbit does not exceed 0.075° of inclination, and

(2) The DBS space station's orbit maintains an apogee less than or equal to 35,806 km above the surface of the Earth, and a perigee greater than or equal to 35,766 km above the surface of the Earth (*i.e.*, an eccentricity of less than 4.7×10^{-4}).

[76 FR 50431, Aug. 15, 2011]

Subpart D—Technical Operations

SOURCE: 58 FR 13421, Mar. 11, 1993, unless otherwise noted.

§ 25.271 Control of transmitting stations.

(a) The licensee of a facility licensed under this part is responsible for the proper operation and maintenance of the station.

(b) The licensee of a transmitting earth station licensed under this part shall ensure that a trained operator is present on the earth station site, or at a designated remote control point for the earth station, at all times that transmissions are being conducted. No operator's license is required for a person to operate or perform maintenance on facilities authorized under this part.

(c) Authority will be granted to operate a transmitting earth station by remote control only on the conditions that:

(1) The parameters of the transmissions of the remote station monitored at the control point, and the operational functions of the remote earth stations that can be controlled by the operator at the control point,

are sufficient to insure that the operations of the remote station(s) are at times in full compliance with the remote station authorization(s);

(2) The earth station facilities are protected by appropriate security measures to prevent unauthorized entry or operations;

(3) Upon detection by the licensee, or upon notification from the Commission of a deviation or upon notification by another licensee of harmful interference, the operation of the remote station shall be immediately suspended by the operator at the control point until the deviation or interference is corrected, except that transmissions concerning the immediate safety of life or property may be conducted for the duration of the emergency; and

(4) The licensee shall have available at all times the technical personnel necessary to perform expeditiously the technical servicing and maintenance of the remote stations.

(5) International VSAT system operators are required to maintain a control point within the United States, or to maintain a point of contact within the United States available 24 hours a day, 7 days a week, with the ability to shut off any earth station within the VSAT network immediately upon notification of harmful interference.

(d) The licensee shall insure that the licensed facilities are properly secured against unauthorized access or use whenever an operator is not present at the transmitter.

(e) The licensee of an NGSO FSS system operating in the 10.7–14.5 GHz bands shall maintain an electronic web site bulletin board to list the satellite ephemeris data, for each satellite in the constellation, using the North American Aerospace Defense Command (NORAD) two-line orbital element format. The orbital elements shall be updated at least once every three days.

[58 FR 13421, Mar. 11, 1993, as amended at 66 FR 10631, Feb. 16, 2001; 70 FR 4787, Jan. 31, 2005; 70 FR 32257, June 2, 2005; 74 FR 47107, Sept. 15, 2009]

§ 25.272 General inter-system coordination procedures.

(a) Each space station licensee in the Fixed-Satellite Service shall establish a satellite network control center

which will have the responsibility to monitor space-to-Earth transmissions in its system. This would indirectly monitor uplink earth station transmissions in its system and to coordinate transmissions in its satellite system with those of other systems to prevent harmful interference incidents or, in the event of a harmful interference incident, to identify the source of the interference and correct the problem promptly.

(b) Each space station licensee shall maintain on file with the Commission and with its Columbia Operations Center in Columbia, Maryland, a current listing of the names, titles, addresses and telephone numbers of the points of contact for resolution of interference problems. Contact personnel should include those responsible for resolution of short term, immediate interference problems at the system control center, and those responsible for long term engineering and technical design issues.

(c) The transmitting earth station licensee shall provide the operator(s) of the satellites, on which the licensee is authorized to transmit, contact telephone numbers for the control center of the earth station and emergency telephone numbers for key personnel; a current file of these contacts shall be maintained at each satellite system control center.

(d) An earth station licensee shall ensure that each of its authorized earth stations complies with the following:

(1) The earth station licensee shall ensure that there is continuously available means of communications between the satellite network control center and the earth station operator or its remote control point as designated by the licensee.

(2) The earth station operator shall notify the satellite network control center and receive permission from the control center before transmitting to the satellite or changing the basic characteristics of a transmission.

(3) The earth station operator shall keep the space station licensee informed of all actual and planned usage.

(4) Upon approval of the satellite network control center, the earth station operator may radiate an RF carrier into the designated transponder. Should improper illumination of the